



Alkaline Batteries

Primex offers Duracell® Duralock® alkaline batteries for use with Primex OneVue™ Analog Clocks. Due to characteristics of alkaline technology, the output of the pack is strong and stable throughout the life of the battery. Alkaline batteries are recommended by Primex for achieving optimal performance and maximum battery life.

D-Cell Alkaline Battery Specifications:

- Nominal Voltage = 1.5 V
- Operating Voltage = 1.6 - 0.75V
- Impedance: 136 m-ohm @ 1kHz
- Typical Weight: 4.9 oz. (139gm)
- Typical Volume: 3.4 in.3 (56.4 cm3)
- Terminals: Flat
- Storage Temperature Range: 41°F to 86°F (5°C to 30 °C)
- Operating Temperature Range: -4°F to 130°F (-20°C to 54°C)
- ANSI: 13A
- IEC: LR20



D-Cell
Alkaline Battery

ALKALINE BATTERIES

Part No.	Description
SNS884	Dual D-cell Alkaline Batteries (qty. 4)

ALKALINE BATTERY LIFE EXPECTANCY

System	Analog Clock	Battery Type	Expected Life
SNS	All	(4) D Cells	4 Years

* Battery life estimates are based under normal operating conditions.

To Learn More:
Call 800.537.0464
Email: info@primexinc.com
primexinc.com



OneVue is a trademark of Primex. The innovative technology software solution for facility and time synchronization monitoring and reporting. All other trademarks are the property of their respective owners.

©2017 Primex. The Primex logo is a registered trademark of Primex.
All Rights Reserved. 1.17